

SUPER A

Polyalphaolefin bitumen membrane (PAO)



DESCRIPTION

Prefabricated waterproofing membrane composed of distilled bitumen and polyalphaolefin polymers (PAO) reinforced with heavy duty, thermostabilised, non-woven spunbonded polyester fabric that gives the membrane high mechanical properties and good dimensional stability (0.3%).

For polyolefin membranes without mineral self-protection consisting of slate, intended to be used as a top layer, always provide for periodic surface protection with protective reflective paint.

The particular formulation of the compound ensures high thermal resistance to the action of UV radiation.

ADVANTAGES

- ✓ High puncture strength
- ✓ Resistance to demanding working situations
- ✓ Excellent mechanical performance
- ✓ High flexibility at low temperatures and hot temp. creep even after aging
- ✓ The PP finish allows for immediate anti UV coating (not essential)
- ✓ Monolayer use

Reinforcement: Non-woven spunbonded polyester fabric

Compound: Polyalphaolefin bitumen

Upper finish: Blue PP

Lower finish: PE Film

Intended use: Upper layer / Underlayer/ Heavy duty lower protection / Foundations / Monolayer

Application method: Blowtorch / Glue / Hot air / Mechanical fixing

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	TESTING METHOD	M.U.	TOLERANCE	VALUE
Thickness	EN 1849-1	mm	MDV - 0.2 mm	4
Maximum tensile strength (L/T)	EN 12311-1	N/50 mm	MDV - 20%	850/650
Flexibility at low temperature	EN 1109	°C	MLV	-25
Creep	EN 1296/1110	°C	MDV - 10°C	140
Load resistance	EN 12730	Kg	MLV	20

PACKAGING

PRODUCT	ROLL SIZE	WEIGHT Kg/m ²	THICKNESS MM	SQUARE METRES PER PALLET	EN STANDARDS
SUPER A	10 m x 1 m	-	4	250	13707-13969

Please refer to the technical data sheet for more information, constant research in the field may result in changes to data content without the producer being obliged to inform all interested parties